


SPECIFICATIONS	
HOUSING MATERIAL/COLOR	TPU/BLACK
CONTACT BODY MATERIAL/COLOR	TPU/BLACK
CONTACT MATERIAL/PLATING	Cu/Au
SEAL MATERIAL	-
NUT MATERIAL/COLOR	Cu/Ni
CABLE SHEATH MATERIAL/COLOR	PVC/BLACK
CABLE CROSS-SECTION (AWG) /SHIELD	3x24AWG/-
BENDING CYCLES/TORSION	-
RATED CURRENT (A)	4A
RATED VOLTAGE (V)	60V
TEMPERATURE RANGE FROM/TO	-40℃~+80℃
DEGREE OF PROTECTINN	IP67 (when properly tightened)



IPC620-D		
CABLE LENGTH (Unit: M)	UPPER (mm)	LOWER (mm)
*≤0.3	25	0
0.3<*≤1.5	50	0
1.5<*≤3	100	0
3<*≤7.5	150	0
>7.5	+5%-0%	0

REV	MARK	DATE	DESC. OF CHG	CHG. BY
/		/	/	/

Tianjin Geneuo Technology Co., Ltd.

THIRD ANGLE PROJECTION		MODEL NO. SZ3-*M/P00			
		ITEM NO.		VER	A
UNITS	SCALE	DWG.	CHK.	APPR.	DATE
mm	1:1	Lishun.Li	Jie.Ma	Deyou.Yang	2025/06/10
DATE	DATE	DATE	DATE	DATE	DATE
2025/07/16	2025/08/06	2025/07/16	2025/08/06	2025/06/10	2025/06/10