



FEMALE END VIEW



1=BN
2=N/C
3=BU
4=BK

SPECIFICATIONS

CONTACT CARRIER MATERIAL/COLOR	PA/BLACK
MOLDED HEAD MATERIAL/COLOR	TPU/BLACK
CONTACT/PLATING	BRASS/GOLD
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL
O-RING MATERIAL	MBR
OPERATING CURRENT	1 A
OPERATING VOLTAGE	60 V
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS (AWG)	3 x 26 AWG
OPERATING TEMPERATURE	-25°C — +80°C
PROTECTION CLASS	IEC IP67



CABLE LENGTH	TOLERANCE
ALL LENGTHS	±4%(OR 50mm) OF LENGTH -0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE
0 - 7mm	± 1.0mm
8 - 29mm	± 1.5mm
30 - 49mm	± 2.0mm
50 - 69mm	± 3.0mm
70 - 100mm	± 4.0mm
over 100mm	± 5.0mm

REV	COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE

UNIT OF MEASUREMENT		MILLIMETER	
Approved:		Date: 2018.4.16	
Process YJF		Scale: 1:1	
Date: 2018.5.24		3RD Angle Projection	
Checked NY		www.gsee-tech.cn	
Date: 2018.5.3		www.gsee-tech.com	
Designed LXH		SOURCE DRAWING-FOR REFERENCE ONLY	
Date: 2018.4.27		REV A	

Tianjin Geneuo Technology Co., Ltd



BK3-*/M/P00