





SPECIFICATIONS		
CONTACT CARRIER MATERIAL/COLOR	PA/BLACK	
MOLDED HEAD MATERIAL/COLOR	TPU/BLACK	
CONTACT/PLATING	BRASS/GOLD	
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL	
O-RING MATERIAL	NBR	
OPERATING CURRENT	1 A	
OPERATING VOLTAGE	60 V	
CONDUCTOR INSULATION MATERIAL	PVC	
NUMBER OF CONDUCTORS (AWG)	4 x 26 AWG	
OPERATING TEMPERATURE	-25°C — +80°C	
PROTECTION CLASS	IEC IP67	



CABLE LENGTH	TOLERANCE
ALL LENGTHS	+4%(OR 50mm) OF LENGTH -0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE
0 - 7mm	± 1.0mm
8 - 29mm	± 1.5mm
30 - 49mm	± 2.0mm
50 - 69mm	± 3.0mm
70 - 100mm	± 4.0mm
over 100mm	± 5.0mm

REV	COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE

UNIT OF MEASUREMENT MILLIMETER		Tianjin Geneuo Technology Co., Ltd		
Approved:	Date:	Description:		
Process YJF	Date: 2018.5.24	BK4 BZ4-*/M/P00		
Checked Y	Date: 2018.5.3			
Designed LXH	Date: 2018.4.27			
3RD Angle Projection	Scale: 1:1			
		www.gsee-tech.cn www.gsee-tech.com		REV A