


FEMALE END VIEW




A.BN
C.RD/BU
E.BK
G.PK
J.GN
L.BU
M.OR
N.GY/BN
O.VT
P.WH
R.RD
S.GY
T.YE
U.TN

SPECIFICATIONS


CONTACT CARRIER MATERIAL/COLOR	PA6/BLACK
MOLDED HEAD MATERIAL/COLOR	TPU/BLACK
CONTACTS	BRASS/GOLD
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL
RATED CURRENT	3A
RATED VOLTAGE	30 V
CONDUCTOR INSULATION MATERIAL/COLOR	PVC/BLACK
NUMBER OF CONDUCTORS (AWG)	14X24AWG
OPERATING TEMPERATURE	-40°C — +80°C
PROTECTION CLASS	IEC IP67

※METERS



CABLE LENGTH	TOLERANCE
ALL LENGTHS	+4%(OR 50mm) OF LENGTH -0%(OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE
0 - 7mm	± 1.0mm
8 - 29mm	± 1.5mm
30 - 49mm	± 2.0mm
50 - 69mm	± 3.0mm
70 - 100mm	± 4.0mm
over 100mm	± 5.0mm

REV	COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE

UNIT OF MEASUREMENT MILLIMETER		Tianjin Geneuo Technology Co.,Ltd				
Approved: Date:		Date: 2019.3.18		Description: DNLK14-14-xM/P00		
Process: Date:		Scale: 1:1				
Checked: Date:		3RD Angle Projection		www.gsee-tech.cn www.gsee-tech.com		REV A
Designed: ZL Date: 2019.4.9				SOURCE DRAWING-FOR REFERENCE ONLY		