


FEMALE END VIEW

The diagram shows the female end view of a shaft-hub assembly. A large circle represents the hub's outer diameter. Inside this circle, there are four smaller circles, each with a crosshair, representing the shaft's cross-section at different angular positions. These positions are labeled with numbers 1, 2, 3, and 4. Position 1 is at the bottom, 2 is at the top-left, 3 is at the top-right, and 4 is at the bottom-right. A curved arrow on the left side of the hub circle indicates a counter-clockwise rotation.

1=BN
2=WH
3=BU
4=BK



SPECIFICATIONS	
CONTACT CARRIER MATERIAL/COLOR	TPU/BLACK
MOLDED HEAD MATERIAL/COLOR	TPU/BLACK
CONTACT/PLATING	BRASS/GOLD
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL
O-RING MATERIAL	FPM/FKM
OPERATING CURRENT	4 A
OPERATING VOLTAGE	250 V
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS (AWG)/SHIELD	4 x 22 AWG/POLYESTER FOIL SHIELD
OPERATING TEMPERATURE	-20°C — +80°C
PROTECTION CLASS	IEC IP67

