







SPECIFICATIONS		
CONTACT CARRIER MATERIAL/COLOR	PA/BLACK	
CONTACTS	BRASS/GOLD	
HOUSING MATERIAL/PLATING	BRASS/NICKEL	
O-RING MATERIAL	NBR	
OPERATING CURRENT	1 A	
OPERATING VOLTAGE	60 V	
CONDUCTOR INSULATION MATERIAL	PVC	
NUMBER OF CONDUCTORS (AWG)	4 x 26 AWG	
OPERATING TEMPERATURE	-20℃ — +85℃	
PROTECTION CLASS	IEC IP67	



CABLE LENGTH	TOLERANCE
ALL LENGTHS	±4%(OR 50mm) OF LENGTH -0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE
0 - 7mm	± 1.0mm
8 - 29mm	± 1.5mm
30 - 49mm	± 2.0mm
50 - 69mm	± 3.0mm
70 - 100mm	± 4.0mm
over 100mm	± 5.0mm

REV	COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE

UNIT OF MEASUREMENT MILLIMETER		Tianjin Geneuo Technology Co., Ltd		GSEE TECH	
Approved: Date:	Date: 2018.4.27	Description : FBZ4-1-※		www.gsee-tech.cn www.gsee-tech.com	
Process YJF Date:2018.5.24	Scale: 1:1				
Checked YJ Date:2018.5.3	3RD Angle Projection				
Designed LH Date:2018.4.27		SOURCE DRAWING-FOR REFERENCE ONLY		REV A	