



FEMALE END VIEW

SUGGESTED PANEL CUT OUT






1=BN
2=WH
3=BU
4=BK
5=GY
6=PK



SPECIFICATIONS

CONTACT CARRIER MATERIAL/COLOR	TPU/BLACK
CONTACT/PLATING	BRASS/GOLD
HOUSING MATERIAL/PLATING	BRASS/NICKEL
O-RING MATERIAL	FKM/NBR
OPERATING CURRENT	2 A
OPERATING VOLTAGE	60 V
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS (AWG)	6 x 24 AWG
OPERATING TEMPERATURE	-20°C — +85°C
PROTECTION CLASS	IEC IP67



CABLE LENGTH	TOLERANCE
ALL LENGTHS	±4%(OR 50mm) OF LENGTH -0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE
0 - 7mm	± 1.0mm
8 - 29mm	± 1.5mm
30 - 49mm	± 2.0mm
50 - 69mm	± 3.0mm
70 - 100mm	± 4.0mm
over 100mm	± 5.0mm

UNIT OF MEASUREMENT
MILLIMETER


Tianjin Geneuo Technology Co., Ltd
www.gsee-tech.cn
www.gsee-tech.com
FEK621-*

Approved: Date: 2018.4.27

Process YJF Date: 2018.5.24 Scale: 1:1

Checked Y Date: 2018.5.3
Designed LXH Date: 2018.4.27

3RD Angle Projection



www.gsee-tech.cn
www.gsee-tech.com

REV A