

PROTECTIO	Pg9	_
OPERATING	-	80
CONDUCTOR		5
OPERATING		7 0 0
OPERATING		$\frac{1}{0}$
O-RING MA		\ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \ \
HOUSING M.		2
CONTACT/F	-	
CONTANCT		
	SUGGESTED PANEL CUT OUT	FEMALE END VIEW

	SPECIFICATIONS
CONTANCT CARRIER MATERIAL/COLOR	TPU/BLACK
CONTACT/PLATING	BRASS/GOLD
HOUSING MATERIAL/PLATING	BRASS/NICKEL
O-RING MATERIAL	FKM/NBR
OPERATING CURRENT	2 A
OPERATING VOLTAGE	60 V
CONDUCTOR CROSS SECTION(AWG)	24 AWG
OPERATING TEMPERATURE	-20°C — +105°C
PROTECTION CLASS	IFC IP67





	SOURCE DRAWING-FOR REFERENCE ONLY	_	Date:2018.4.27	DATE	BY CHECKED DATE	ВҮ	REV COUNT DESCRIPTION OF REVISIONS	COUNT	REV
>	www.ysee_lecli.com	Projection							
K-<			Date:2018.5.3						
)	www deestern on		Checked:WY						
		l-1	Pairie di Cibie di						
	FER82-L	Scale: 1.1	Process:YJF						
	1	2010.4.27	Pale						
	Description:	Date: 2018 / 27	/ed:						
1	Technology Co.,Ltd	Tianjin Geneuo Techi	MILLIMETER						
)							
G M M			UNIT OF MEASUREMENT						