






MALE END VIEW	SUGGESTED PANEL CUT OUT	SPECIFICATIONS	
 1=BN 2=WH 3=BU 4=BK		CONTACT CARRIER MATERIAL/COLOR	TPU/BLACK
		CONTACT/PLATING	BRASS/GOLD
		HOUSING MATERIAL/PLATING	BRASS/NICKEL
		O-RING MATERIAL	NBR
		OPERATING CURRENT	4 A
		OPERATING VOLTAGE	250 V
		CONDUCTOR INSULATION MATERIAL	PVC
		NUMBER OF CONDUCTORS (AWG)	4 x 22 AWG
		OPERATING TEMPERATURE	-20°C — +85°C
		PROTECTION CLASS	IEC IP67



CABLE LENGTH	TOLERANCE
ALL LENGTHS	+4%(OR 50mm) OF LENGTH -0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE
0 - 7mm	± 1.0mm
8 - 29mm	± 1.5mm
30 - 49mm	± 2.0mm
50 - 69mm	± 3.0mm
70 - 100mm	± 4.0mm
over 100mm	± 5.0mm

REV	COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE

UNIT OF MEASUREMENT				
MILLIMETER		Tianjin Geneuo Technology Co.,Ltd		
Approved: Date:	Date: 2018.4.27	Description: FEZ42-*		REV A
Process:YJ F Date:2018.5.24	Scale: 1:1			
Checked:WY Date:2018.5.3	3RD Angle Projection 	www.gsee-tech.cn www.gsee-tech.com		
Designed:LXH Date:2018.4.27		SOURCE DRAWING-FOR REFERENCE ONLY		