






FEMALE END VIEW	TYPICAL PANEL CUTOUT	SPECIFICATIONS	
		CONTACT CARRIER MATERIAL/COLOR	PBT/WHITE
		CONTACT MATERIAL/PLATING	BRASS/GOLD
		COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL
		SEALING RING MATERIAL	NBR
		RATED CURRENT	6 A
		RATED VOLTAGE	300 V
		MAX.CONDUCTORS SIZE	11x18AWG
		OPERATING TEMPERATURE	-40°C — +85°C
		PROTECTION CLASS	IEC IP67



CABLE LENGTH	TOLERANCE
ALL LENGTHS	+4%(OR 50mm) OF LENGTH -0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE
0 - 7mm	± 1.0mm
8 - 29mm	± 1.5mm
30 - 49mm	± 2.0mm
50 - 69mm	± 3.0mm
70 - 100mm	± 4.0mm
over 100mm	± 5.0mm

REV	COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE

UNIT OF MEASUREMENT		 Tianjin Geneuo Technology Co.,Ltd		
MILLIMETER				
Approved: Date:	Date: 2019.3.26	Description: FGWK12-112-x/M20		
Process: Date:	Scale: 2:1			
Checked: Date:	3RD Angle Projection 	www.gsee-tech.cn www.gsee-tech.com		REV A
Designed: ZL Date: 2019.5.28		SOURCE DRAWING-FOR REFERENCE ONLY		