



FEMALE END VIEW



1. BN
2. BU
3. WH
4. GN/YE
5. OG
6. YE
7. GY
8. PK
9. RD
10. BN/WH
11. BU/WH
12. GN/WH


SPECIFICATIONS

CONTACT CARRIER MATERIAL/COLOR	PBT/WHITE
MOLDED HEAD MATERIAL/COLOR	TPU/BLACK
CONTACT MATERIAL/PLATING	BRASS/SILVER
COUPLING NUT MATERIAL/PLATING	ZINC ALLOY/NICKEL
RATED CURRENT	6 A
RATED VOLTAGE	300 V
OUTER CABLR JACKET MATERIAL/COLOR	PVC/BLACK
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS (AWG)	12X18AWG
OPERATING TEMPERATURE	-40°C — +80°C
PROTECTION CLASS	IEC IP67



CABLE LENGTH	TOLERANCE
ALL LENGTHS	+4%(OR 50mm) OF LENGTH -0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE
0 - 7mm	± 1.0mm
8 - 29mm	± 1.5mm
30 - 49mm	± 2.0mm
50 - 69mm	± 3.0mm
70 - 100mm	± 4.0mm
over 100mm	± 5.0mm

REV	COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE

UNIT OF MEASUREMENT MILLIMETER		 Tianjin Geneuo Technology Co.,Ltd	
Approved: Date:	Date: 2019.3.18	Description: GNLK12-12R-xM/P00	
Process: Date:	Scale: 1:1		
Checked: Date:	3RD Angle Projection		www.gsee-tech.cn www.gsee-tech.com
Designed: ZL Date: 2019.3.15			
SOURCE DRAWING-FOR REFERENCE ONLY			REV A