


MALE END VIEW

1. WH
2. GN
3. YE
4. GY
5. PK
6. RD
7. BK
8. VT
9. BU
10. BU
11. BN
12. GN/YE


1. WH
2. GN
3. YE
4. GY
5. PK
6. RD
7. BK
8. VT
9. BU
10. BU
11. BN
12. GN/YE

SPECIFICATIONS	
CONTACT CARRIER MATERIAL/COLOR	PBT/WHITE
MOLDED HEAD MATERIAL/COLOR	TPU/BLACK
CONTACT MATERIAL/PLATING	BRASS/GOLD
COUPLING NUT MATERIAL/PLATING	ZINC ALLOY/NICKEL
RATED CURRENT	6 A
RATED VOLTAGE	300 V
OUTER CABLE JACKET MATERIAL/COLOR	PVC/BLACK
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS (AWG)	1X18AWG
OPERATING TEMPERATURE	-40°C — +80°C
PROTECTION CLASS	IEC IP67



CABLE LENGTH	TOLERANCE
ALL LENGTHS	+4% (OR 50mm) OF LENGTH -0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE
0 - 7mm	± 10mm
8 - 29mm	± 15mm
30 - 49mm	± 20mm
50 - 69mm	± 30mm
70 - 100mm	± 40mm
over 100mm	± 50mm

REV	COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE

UNIT OF MEASUREMENT		 Tianjin Geneuo Technology Co.,Ltd		
MILLIMETER				
Approved: Date:	Date: 2019.3.15	Description: GNZ12-11-xM/P00		
Process: Date:	Scale: 1:1			
Checked: Date:	3RD Angle Projection 	www.gsee-tech.cn www.gsee-tech.com		REV A
Designed: ZL Date: 2019.3.15		SOURCE DRAWING-FOR REFERENCE ONLY		