



MALE END VIEW



- 1. WH
- 2. GN
- 3. YE
- 4. GY
- 5. PK
- 6. RD
- 7. BK
- 8. VT
- 9. BU
- 10. BU
- 11. BN
- 12. GN/YE


SPECIFICATIONS

CONTACT CARRIER MATERIAL/COLOR	PBT/WHITE
MOLDED HEAD MATERIAL/COLOR	TPU/BLACK
CONTACT MATERIAL/PLATING	BRASS/GOLD
COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL
RATED CURRENT	6 A
RATED VOLTAGE	300 V
OUTER CABLE JACKET MATERIAL/COLOR	PVC/BLACK
CONDUCTOR INSULATION MATERIAL	PVC
NUMBER OF CONDUCTORS (AWG)	11X18AWG
OPERATING TEMPERATURE	-40°C — +80°C
PROTECTION CLASS	IEC IP67



CABLE LENGTH	TOLERANCE
ALL LENGTHS	+4%(OR 50mm) OF LENGTH -0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE
0 - 7mm	± 1.0mm
8 - 29mm	± 1.5mm
30 - 49mm	± 2.0mm
50 - 69mm	± 3.0mm
70 - 100mm	± 4.0mm
over 100mm	± 5.0mm

REV	COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE

UNIT OF MEASUREMENT		GT GSEE TECH Tianjin Geneuo Technology Co.,Ltd			
MILLIMETER					
Approved: Date:	Date: 2019.3.15	Description: GWZ12-11-xM/P00			
Process: Date:	Scale: 1:1				
Checked: Date:	3RD Angle Projection		www.gsee-tech.cn www.gsee-tech.com	REV A	
Designed: ZL Date: 2019.3.15			SOURCE DRAWING-FOR REFERENCE ONLY		