



FEMALE END VIEW 1=BN 2=WH 3=BU 4=BK PE=GN/YE	SPECIFICATIONS	
	CONTANCT CARRIER MATERIAL/COLOR	TPU/BLACK
	MOLDED HEAD MATERIAL/COLOR	TPU/BLACK
	CONTACT/PLATING	BRASS/GOLD
	COUPLING NUT MATERIAL/PLATING	BRASS/NICKEL
	OPERATING CURRENT	16 A
	OPERATING VOLTAGE	63 V
	CONDUCTOR INSULATION MATERIAL	PVC
	NUMBER OF CONDUCTORS (AWG)/SHIELD	5 x 16 AWG
	OPERATING TEMPERATURE	-20 ° C — +80 ° C
	PROTECTION CLASS	IEC IP67



CABLE LENGTH	TOLERANCE
ALL LENGTHS	+4%(OR 50mm) OF LENGTH -0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE
0 - 7mm	± 1.0mm
8 - 29mm	± 1.5mm
30 - 49mm	± 2.0mm
50 - 69mm	± 3.0mm
70 - 100mm	± 4.0mm
over 100mm	± 5.0mm

REV	COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE

UNIT OF MEASUREMENT		GSEE TECH Tianjin Geneuo Technology Co.,Ltd		
MILLIMETER				
Approved: Date:	Date: 2018.4.16	Description: PL-EK5- M/S10		
Process:YJ F Date:2018.5.24	Scale: 1:1			
Checked:WY Date:2018.5.3	3RD Angle Projection		www.gsee-tech.cn www.gsee-tech.com	REV A
Designed:LXH Date:2018.4.27			SOURCE DRAWING-FOR REFERENCE ONLY	