




FEMALE END VIEW




SPECIFICATIONS

CONTACT CARRIER MATERIAL/COLOR	TPU/BLACK
CONTACT MATERIAL/PLATING	BRASS/GOLD
HOUSING MATERIAL/PLATING	BRASS/NICKEL
O-RING MATERIAL	NBR
OPERATING CURRENT	3A
OPERATING VOLTAGE	60 V
CONDUCTOR INSULATION MATERIAL	PVC
OUTER JACKET MATERIAL	PVC
NUMBER OF CONDUCTORS (AWG)	4 x 24 AWG
OPERATING TEMPERATURE	-25°C — +80°C
PROTECTION CLASS	IEC IP67



CABLE LENGTH	TOLERANCE
ALL LENGTHS	+4%(OR 50mm) OF LENGTH -0% (OR 0mm) OF LENGTH WHICHEVER IS GREATER
STRIP LENGTH	TOLERANCE
0 - 7mm	± 1.0mm
8 - 29mm	± 1.5mm
30 - 49mm	± 2.0mm
50 - 69mm	± 3.0mm
70 - 100mm	± 4.0mm
over 100mm	± 5.0mm

REV	COUNT	DESCRIPTION OF REVISIONS	BY	CHECKED	DATE

UNIT OF MEASUREMENT MILLIMETER		Tianjin Geneuo Technology Co.,Ltd				
Approved: Date:		Date: 2018.08.08		Description : RLK4-※M/P00		
Process:YJF Date:2018.08.22		Scale: 1:1				
Checked: Date:		3RD Angle Projection		www.gsee-tech.cn www.gsee-tech.com		REV A
Designed:LHT Date:2018.08.08				SOURCE DRAWING-FOR REFERENCE ONLY		